



FUEL MANAGEMENT SYSTEMS



DISPENSERS



KITS



PUMPS



METERS



NOZZLES

SELF 2000 / SELF 3000

FEATURES

- MANUAL
- VERSATILE
- HIGH EFFICIENCY
- LEVER PROTECTION

The PIUSI SELF 2000 / SELF 3000 manual nozzles perform the maximum efficiency thanks to the low-flow resistance and the wide range of applications including transfer systems run by gravity. They are supplied with removable lever protection and connectors.



SELF 2000 DIESEL



SELF 3000 DIESEL/GASOLINE



KUNSTSTOFF-ZAPFVENTIL WASSER/DIESEL

PERFORMANCE

UP TO

150 L/MIN

FLOW RATE

20/25MM

OD SPOUT

SELF 2000 / SELF 3000



PACKAGING

| CODE | WEIGHT | | PACKAGING | | | N. BOXES / EUROPALLET | |
|-----------|--------|-----|-------------|-----------|---------|-----------------------|--|
| | KG | LBS | MM | INCH | PCS/BOX | | |
| 00063900A | 0,7 | 1,5 | 400X250X200 | 16X11X7,8 | 1 | | |
| 00064900A | 0,7 | 1,5 | 400X250X200 | 16X11X7,8 | 1 | | |
| 00064902A | 0,7 | 1,5 | 400X250X200 | 16X11X7,8 | 1 | | |
| 00065001A | 0,7 | 1,5 | 400X250X200 | 16X11X7,8 | 1 | | |
| 00065600A | 0,7 | 1,5 | 400X250X200 | 16X11X7,8 | 1 | | |
| FO0641120 | 0,7 | 1,5 | 400X250X200 | 16X11X7,8 | 1 | | |
| FO0641130 | 0,7 | 1,5 | 400X250X200 | 16X11X7,8 | 1 | | |
| FO065000A | 0,7 | 1,5 | 400X250X200 | 16X11X7,8 | 1 | | |
| FO0650020 | 0,7 | 1,5 | 400X250X200 | 16X11X7,8 | 1 | | |
| FO063000A | 0,3 | 0,7 | - | - | 1 | | |
| FO0641B00 | 0,7 | 1,5 | 400X250X200 | 16X11X7,8 | 1 | | |



FILTRATION



TANK MONITORING



HOSE REEL



ACCESSORIES



MERCHANDISE

PIUSI



ANY BIODIESEL



AIR



ANTIFREEZE



AdBlue®



BIODIESEL



DIESEL



FOOD



GASOLINE



GREASE



KEROSENE



OIL



WATER



WINDSCREEN

CHART




IN THE BOX

- SELF 2000/ SELF 3000 NOZZLE

DETAILS



LEVER PROTECTION



ROTATING SWIVEL

MATERIALS

SELF 2000 & SELF 3000

- BODY: ALUMINIUM
- SEAL: NBR70SH

PLASTIC NOZZLE

- BODY: PP+FV
- SEAL: NBR

TECHNICAL DATA

| CODE | DESCRIPTION | FLUIDS TYPE | FLOW RATE | | INLET | | SPOUT |
|-----------|--|-------------|-----------|-----|------------------|----------|-----------|
| | | | L/MIN | GPM | SWIVEL (THREADS) | Ø BSP | EXT. Ø MM |
| 00063900A | SELF 2000 1" BSP UNLEADED | D G O | 120 | 32 | INTERNAL | 1" BSP | 20 |
| 00064900A | SELF 2000 3/4" BSP | D O | 120 | 32 | INTERNAL | 3/4" BSP | 25 |
| 00064902A | SELF 2000 3/4" BSP UNLEADED | D G O | 120 | 32 | INTERNAL | 3/4" BSP | 20 |
| 00065001A | SELF 3000 1" BSP UNLEADED | D O G | 150 | 40 | INTERNAL | 1" BSP | 20 |
| 00065600A | SELF 2000 1" BSP SPOUT 25 MM | D O | 120 | 32 | INTERNAL | 1" BSP | 25 |
| FO0641120 | SELF 2000 W/HOSE TAIL D.20 SPOUT 25 MM | D O | 120 | 32 | INTERNAL | 3/4" BSP | 25 |
| FO0641130 | SELF 2000 1" BSP | D O | 120 | 32 | INTERNAL | 1" BSP | 25 |
| FO065000A | SELF 3000 1" BSP LEADED SPOUT | D O | 150 | 40 | INTERNAL | 1" BSP | 25 |
| FO0650020 | SELF 3000 1" BSP LEADED SPOUT S/P | D G O W | 150 | 40 | INTERNAL | 1" BSP | 25 |
| FO063000A | PLASTIC NOZZLE BLACK W/SWIVEL 1" BSP | D O W | 80 | 21 | INTERNAL | 1" BSP | 34 |
| FO0641B00 | SELF 2000 1" BSP B100 | B | 120 | 32 | INTERNAL | 1" BSP | 20 |