Company name:	MATO GmbH & Co.KG	
Street/POB-No.:	Benzstr. 16-24	
Postal Code, city:	63165 Mühlheim/Main	
WWW:	www.mato.de	
E-mail:	mato.germany@mato.de	
Telephone:	+49 (0)6108-906-0	
Telefax:	+49 (0)6108-906-120	
Department responsible for information:		
	Herr Gerold Isokeit,	

Telephone: +49 (0)6108-906-135, e-mail isokeit@mato.de

#### 1.4 Emergency telephone number

GIZ-Nord, Göttingen, Germany, Telephone: +49 551-19240 Transport: CONSULTANK Lutz Harder GmbH (Contract QUALI003) Telephone: +49 (0)178-4337434 (from USA: 01149 178 4337434)

## **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### Classification according to EC regulation 1272/2008 (CLP)

This mixture is classified as not hazardous.

#### 2.2 Label elements

#### Labelling (CLP)

Hazard statements: not applical

Precautionary statements: not applicable

#### Special labelling

EUH210 Safety data sheet available on request.

#### 2.3 Other hazards

Special danger of slipping by leaking/spilling product.

Results of PBT and vPvB assessment:

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

## High Temp EP-2LHT

SAFETY DATA SHEET

Material number 72708

No. 2015/830

Revision date: 13/11/2020 Version: 3.0 en-GB,IE Language: Date of print: 18/11/2020

Page:

1 of 9

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU)

#### **1.1 Product identifier**

mato

Trade name: High Temp EP-2LHT

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

General use: Lubricating grease Reserved for industrial and professional use.

#### 1.3 Details of the supplier of the safety data sheet

ble			

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Page:

## High Temp EP-2LHT

Material number 72708

2 of 9

## **SECTION 3: Composition / information on ingredients**

#### 3.1 Substances: not applicable

mato

#### 3.2 Mixtures

#### Chemical characterisation: Lubricating grease.

Mixture of the substance mentioned below with non-hazardous additions:

Hazardous ingredients:

Ingredient	Designation	Content	Classification
REACH 01-2120119814-57-xxxx EC No. 254-184-4 CAS 38900-29-7	Dilithium azelate	2.5 - 5 %	Acute Tox. 4; H302.

Full text of H- and EUH-statements: see section 16.

Information about mineral oil: < 3% dimethylsulfoxide (DMSO) extract (IP 346) Additional information:

### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General information:	If medical advice is needed, have product container or label at hand. Take off contaminated clothing and wash it before reuse.		
In case of inhalation:	If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Seek medical treatment in case of troubles.		
Following skin contact:	Thoroughly wash skin with soap and water. In case of skin reactions, consult a physician.		
After eye contact:	Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an opthalmologist.		
After swallowing:	Do not induce vomiting. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. In the event of discomfort seek medical treatment.		
4.2 Most important symptoms and effects, both acute and delayed			

#### Most important symptoms and effects, both acute and delayed

Inhaling can lead to irritations of the respiratory tract and mucous membrane. Frequent or prolonged skin contact may cause irritation and inflammation.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media:

Foam, extinguishing powder and carbon dioxide.

Extinguishing media which must not be used for safety reasons:

Full water jet

#### 5.2 Special hazards arising from the substance or mixture

Combustible. May form dangerous gases and vapours in case of fire.

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

## High Temp EP-2LHT

Material number 72708

Page:

3 of 9

#### 5.3 Advice for firefighters

mato

Special protective equipment for firefighters:

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information: Hazchem-Code: -

Heating causes rise in pressure with risk of bursting. Cool endangered containers with water spray and, if possible, remove from danger zone. Use water spray jet to knock down vapours. Do not breathe fumes. Do not allow fire water to penetrate into surface or ground water.

## **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. Do not breathe mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Wear appropriate protective equipment. Take off contaminated clothing and wash it before reuse. Wash hands before breaks and after work. Do not eat, drink or smoke when using this product.

#### 6.2 Environmental precautions

Do not allow to penetrate into soil, waterbodies or drains. If necessary notify appropriate authorities.

#### 6.3 Methods and material for containment and cleaning up

Plug leak if safely possible. Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Final cleaning. Dispose of waste according to applicable legislation.

Additional information: Special danger of slipping by leaking/spilling product.

#### 6.4 Reference to other sections

Refer additionally to section 8 and 13.

## **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Advices on safe handling: Provide adequate ventilation, and local exhaust as needed. Do not breathe mist/vapours/spray. Vapours/aerosols must be exhausted directly at the point of origin. Do not get in eyes, on skin, or on clothing. Wear appropriate protective equipment. Take off contaminated clothing and wash it before reuse. Wash hands before breaks and after work. Do not eat, drink or smoke when using this product. Have eye wash bottle or eye rinse ready at work place.

Precautions against fire and explosion:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take action to prevent static discharges.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers:

	Keep container dry, tightly closed and store at cool and aired place. storage temperature: < 45 °C.
Hints on joint storage:	Do not store together with strong oxidizing agents. Keep away from food, drink and animal feedingstuffs.

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

## High Temp EP-2LHT

Material number 72708

Page:

4 of 9

#### 7.3 Specific end use(s)

mato

No information available.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Occupational exposure limit values:	

Туре	Limit value
Great Britain: MEL/OES-STEL	10 mg/m³ (Oil mist)
Great Britain: MEL/OES-TWA	5 mg/m³ (Oil mist)
Ireland: 8 hours	5 mg/m <sup>3</sup> (Oil mist mineral, inhalable fraction)

#### 8.2 Exposure controls

Provide good ventilation and/or an exhaust system in the work area.

#### Personal protection equipment

#### Occupational exposure controls

Respiratory protection:	If vapours form, use respiratory protection. Use filter type A (= against vapours of organic substances) according to EN 14387. The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.	
Hand protection:	Protective gloves according to EN 374. Glove material: Nitrile rubber - Layer thickness: >= 0.38 mm Breakthrough time: >480 min. Observe glove manufacturer's instructions concerning penetrability and breakthrough time.	
Eye protection:	Tightly sealed goggles according to EN 166.	
Body protection:	Wear suitable protective clothing.	
General protection and hygiene measures:		
	Do not breathe mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Wear appropriate protective equipment. Take off contaminated clothing and wash it before	

appropriate protective equipment. Take off contaminated clothing and wash it before reuse. Wash hands before breaks and after work. Do not eat, drink or smoke when using this product. Have eye wash bottle or eye rinse ready at work place.

#### **Environmental exposure controls**

Refer to "6.2 Environmental precautions".

## **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Appearance:	Physical state at 20 °C and 101.3 kPa: liquid
	Form: semi-solid, smooth
	Colour: yellow-brown
Odour:	like petroleum
Odour threshold:	No data available

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date:	13/11/2020
Version:	3.0
Language:	en-GB,IE
Date of print:	18/11/2020

#### High Temp EP-2LHT Material number 72708

Page:	5 of 9
n form explosive	1
-	n form explosive

#### 9.2 Other information

mato

Additional information:

No data available

## **SECTION 10: Stability and reactivity**

#### **10.1 Reactivity**

Refer to subsection "Possilbility of hazardous reactions".

#### 10.2 Chemical stability

Stable under recommended storage conditions.

#### 10.3 Possibility of hazardous reactions

No dangerous reactions with proper and specified storage and handling.

#### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take action to prevent static discharges.

#### 10.5 Incompatible materials

Strong oxidizing agents

#### 10.6 Hazardous decomposition products

 No decomposition when used properly.

 Thermal decomposition:
 No data available

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

0
0
Ε
0

# High Temp EP-2LHT Material number 72708

Page:

6 of 9

## **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

mato

Toxicological effects:	The statements are derived from the properties of the single components. No toxicological data is available for the product as such.
	Acute toxicity (oral): Based on available data, the classification criteria are not met. ATEmix calculated: 4,094 mg/kg
	Acute toxicity (dermal): Based on available data, the classification criteria are not met. ATEmix calculated: 4,236 mg/kg
	Acute toxicity (inhalative): Based on available data, the classification criteria are not met.
	Skin corrosion/irritation: Based on available data, the classification criteria are not met.
	Serious eye damage/irritation: Based on available data, the classification criteria are not met.
	Sensitisation to the respiratory tract: Based on available data, the classification criteria are not met.
	Skin sensitisation: Based on available data, the classification criteria are not met.
	Germ cell mutagenicity/Genotoxicity: Based on available data, the classification criteria are not met.
	Carcinogenicity: Based on available data, the classification criteria are not met.
	Reproductive toxicity: Based on available data, the classification criteria are not met.
	Effects on or via lactation: Lack of data.
	Specific target organ toxicity (single exposure): Based on available data, the classification criteria are not met.
	Specific target organ toxicity (repeated exposure): Based on available data, the classification criteria are not met.
	Aspiration hazard: Based on available data, the classification criteria are not met.
Other information:	Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal.
	Used oil: Evidence for possible carcinogenic effects in experimental animals existent.
Symptoms	
-)	In case of inhalation:
	Overheating released mist or vapours can irritate the respiratory tracts.
	Other symptoms: Cough, respiratory complaints, dizziness, nausea, vomiting, headache
	In case of ingestion: Following symptoms can occur depending on degree of seriousness: Nausea,
	gastrointestinal complaints, vomiting.
	After contact with skin:
	Frequent or prolonged skin contact may cause irritation and inflammation.
	Prolonged/repetitive skin contact may cause skin defattening or dermatitis.
	Other symptoms: skin rash, irritation. After eye contact: Upon direct contact with eyes may cause burning, tearing, redness.
	,, ,, ,

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

# Revision date: 13/11/2020 Version: 3.0 Language: en-GB,IE Date of print: 18/11/2020

Page:

## High Temp EP-2LHT

Material number 72708

7 of 9

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

Further details: No data available

mato

#### 12.2 Persistence and degradability

Further details: Product is not readily biodegradable.

#### 12.3 Bioaccumulative potential

Significant bioaccumulation potential is not to be expected. Partition coefficient: n-octanol/water:

No data available

#### 12.4 Mobility in soil

Floats on the water.

#### 12.5 Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

#### 12.6 Other adverse effects

General information: Do not allow to enter into ground-water, surface water or drains.

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

#### Product

Waste key number:13 08 99\* =Oil wastes not otherwise specified<br/>\* = Evidence for disposal must be provided.Recommendation:Dispose of waste according to applicable legislation.

#### **Contaminated packaging**

Recommendation: Dispose of waste according to applicable legislation. Handle contaminated packages in the same way as the substance itself. Non-contaminated packages may be recycled.

## **SECTION 14: Transport information**

#### 14.1 UN number

ADR/RID, IMDG, IATA-DGR:

not applicable

#### 14.2 UN proper shipping name

ADR/RID, IMDG, IATA-DGR:

Not restricted

#### 14.3 Transport hazard class(es)

ADR/RID, IMDG, IATA-DGR:

not applicable

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

## High Temp EP-2LHT

Material number 72708

Revision date:13/11/2020Version:3.0Language:en-GB,IEDate of print:18/11/2020

Page:

8 of 9

#### 14.4 Packing group

ADR/RID, IMDG, IATA-DGR:

not applicable

#### 14.5 Environmental hazards

mato

Marine pollutant:

#### 14.6 Special precautions for user

no

No dangerous good in sense of these transport regulations.

#### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

## **SECTION 15: Regulatory information**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### National regulations - Great Britain

Hazchem-Code:

No data available

#### **15.2 Chemical Safety Assessment**

For this mixture a chemical safety assessment is not required.

## **SECTION 16: Other information**

#### **Further information**

Wording of the H-phrases under paragraph 2 and 3:

H302 = Harmful if swallowed.

EUH210 = Safety data sheet available on request.

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date:	13/11/2020
Version:	3.0
Language:	en-GB,IE
Date of print:	18/11/2020

9 of 9

Page:

## High Temp EP-2LHT

Material	number 72708	

mato

Abbreviations and acronyms:		
	ADN: European Agreement concerning the International Carriage of Dangerous Goods by	
	Inland Waterways	
	ADR: European Agreement concerning the International Carriage of Dangerous Goods by	
	Road	
	AS/NZS: Australian Standards/New Zealand Standards	
	CAS: Chemical Abstracts Service	
	CFR: Code of Federal Regulations	
	CLP: Classification, Labelling and Packaging	
	DMEL: Derived minimal effect level	
	DNEL: Derived no-effect level	
	EC: European Community	
	EN: European Standard	
	EU: European Union	
	IATA: International Air Transport Association IBC Code: International Code for the Construction and Equipment of Ships carrying	
	Dangerous Chemicals in Bulk	
	IMDG Code: International Maritime Dangerous Goods Code	
	MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution	
	from Ships	
	OSHA: Occupational Safety and Health Administration	
	PBT: Persistent, bioaccumulative and toxic	
	PNEC: Predicted no-effect concentration	
	REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals	
	RID: Regulations Concerning the International Carriage of Dangerous Goods by Rail	
	vPvB: Very persistent and very bioaccumulative	
Reason of change:	Changes in section 2: Classification, labelling	
-	Changes in section 3: Composition / Information on ingredients	
	General revision	
Date of first version:	26/11/2015	
Department issuing data sheet		

Contact person: see section 1: Department responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.