



Engineered for transferring corrosive chemicals associated with the water treatment industry. Robust CPVC offers excellent durability and chemical resistance.

### Technical Specifications

- Package Includes:**..... Motor, Pump Tube, Hose, Wall Bracket, Barrel Adaptor & Hand Nozzle
- Motor Type:**..... 230V, 950 W, IP54, Variable Speed Drive
- Pump Tube Material:**..... CPVC, Hastelloy C-276, Carbon Graphite
- Immersion Length:**..... 39" (1000 mm) or 47" (1200 mm)
- Discharge Hose:** .....PVC, 1,8 m, 1" (25 mm) I.D.
- Hand Nozzle Material:** .....Polypropylene, Viton
- Maximum Flow Rate:**.....67 L/min based on water
- Maximum Viscosity:** ..... 1500 cps (mPas)
- Maximum Temperature:** ..... 80°C
- Shipping Weight:** .....9,97 kg



### DRUM & IBC tanks

Package P/N	Motor	Power	Pump Tube
9550	SPE-950V	950 W	SP-CPVC-39
9551	SPE-950V	950 W	SP-CPVC-47



**Warning: This pump is not suitable for use with Flammable/Combustible liquids.**

\*Note: When pumping viscosities over 1,000 cps, pump must be used intermittently to avoid potential premature failure and/or damage.