









SELF SERVICE B.SMART

FEATURES

- FUEL MANAGEMENT SYSTEM B.SMART INTEGRATED
- NO SOFTWARE INSTALLATION REQUIRED
- SUITABLE FOR FLEETS OF ALL SIZES
- REAL TIME FEEDBACK FROM ANYWHERE
- BUILT-IN FILTER
- ALL-IN-ONE EQUIPMENT
- · COMPACT DESIGN
- KIT UPGRADE 1.0/2018 AVAILABLE

Top quality diesel dispenser by PIUSI, combined with the innovative B.SMART fuel management system: this is the core of the new SELF SERVICE B.SMART. A complete device specifically engineered to fit all diesel transfer needs while performing all the features of a fuel management software in terms of monitoring, controlling and managing the consumption of fuel by the fleet.

This dispenser performs: a sturdy design to ensure proper function in any working condition, a vane pump with incorporated bypass for a high flow rate (up to 90 I/min) and an oval gear meter to ensure maximum precision in measurement. An automatic nozzle with swivel connection, ergonomic and easy to handle, and a water absorption filter completes its components.

PERFORMANCE









PACKAGING												
CODE	WEI	GHT		N. BOXES / EUROPALLET								
	KG	LBS	ММ	INCH	PCS/BOX	×						
F00748010	57	125	1480X490X400	58,3X19,3X15,7	1	-	-					
F00748000	61	133	1480X490X400	58,3X19,3X15,7	1	-	-					



























TEMPERATURE 20°C
















CHART

E120 / PANTHER 72



IN THE BOX


- SELF SERVICE B.SMART DISPENSER
- DELIVERY HOSE
- AUTOMATIC NOZZLE
- DRIVER ACCESS ADD-ON
- INSTRUCTION MANUAL

DETAILS






≈3B.SM4RT





DIMENSIONS



Dimensions expressed in millimeters

MATERIALS

- PUMPS: **PANTHER 72 / E120**
- METER: K600/3
- NOZZLE: AUTOMATIC NOZZLE
- FILTER: WATER CAPTOR

TECHNICAL DATA															
CODE	DESCRIPTION	FLUIDS TYPE	FLOW RATE		VOLTAGE			PUMP	METER	NOZZLE	FILTER	INLET	нс	OSE	
			L/MIN	GPM	AC \	/./HZ /OLT	POWER WATT	AMP. MAX.	TYPE	TYPE	TYPE	H2O FILTER	BSP	LENGTH	ø
F00748010	SELF SERVICE 70 230V B.SMART 10 DRIVERS	D	70	18	230 V	50 HZ	550 W	3,3 A	PANTHER 72	K600/3	A80	30 μΜ	11/2"	4M	25MM
F00748000	SELF SERVICE 100 230V B.SMART 10 DRIVERS	D	90	24	230 V	50 HZ	1150 W	5,7 A	E120	K600/3	A120	30 μΜ	11/2"	4M	25MM