











*K1*50

FEATURES

- · HEAVY DUTY CONDITIONS
- · HIGH FLOW RATE
- BURSTING PRESSURE 28 BAR
- · EASY READING
- 4 FLOW DIRECTIONS

K15O is expressly engineered to meet the market requirements of a meter suitable for flow rates superior than 12O I/min and that can be used both for fluids such as diesel and biodiesel, as well as in potentially explosives atmosphere; with gasoline for example. K15O is easy to calibrate and ready to use; its aluminium cover and sturdy body make this meter suitable for a wide arrange of application while guaranteeing the same precision and quality that have always featured PIUSI equipment. The mechanical display allows to read quickly the quantity dispensed. It can be installed everywhere thanks to the (optional) 1,5" flange kit.

PERFORMANCE

UP TO

25-150

L/MIN

FLOW RATE

3,5 BAR
MAX
OPERATING PRESSURE

± 1%

O,3%





| PACKAGING | | | | | | | | | | | | | |
|-----------|--------|------|-------------|------------------|---------|-----|-----|--|--|--|--|--|--|
| | WEIGHT | | | BOXES/EUROPALLET | | | | | | | | | |
| CODE | KG | LBS | мм | INCH | PCS/BOX | × | 4 | | | | | | |
| F00554A00 | 2,38 | 5,25 | 185X185X17O | 7,28X7,28X6,69 | 1 | 192 | 240 | | | | | | |
| F00554B00 | 2,38 | 5,25 | 185X185X17O | 7,28X7,28X6,69 | 1 | 192 | 240 | | | | | | |
| F00554C00 | 2,38 | 5,25 | 185X185X17O | 7,28X7,28X6,69 | 1 | 192 | 240 | | | | | | |
| F00554D00 | 2,38 | 5,25 | 185X185X17O | 7,28X7,28X6,69 | 1 | 192 | 240 | | | | | | |













TANK MONITORING

HOSE REEL

ACCESSORIES

MERCHANDISE

























CHART

K150



IN THE BOX

- · K150 METER
- · INSTRUCTION MANUAL

DETAILS







METALLIC COVER

DIMENSIONS

MATERIALS

- BODY AND COVER: ALUMINIUM
- · NUTATING DISK CHAMBER: TECHNOPOLYMER





Dimensions expressed in millimeters

| TECHNICAL DATA | | | | | | | | | | | | |
|----------------|----------------------------------|-------------|-----------|--------|-------------|----------|-----|--------------|--|--|--|--|
| CODE | DESCRIPTION | FLUIDS TYPE | FLOW RATE | | FLOW | PRESSURE | | INLET/OUTLET | | | | |
| | | | L/MIN | GPM | DIRECTIONS | BAR | PSI | BSP | | | | |
| F00554A00 | K150 METER LITERS - 1" BSP VER.A | D | 25-150 | 6,6-40 | 4 | 3,5 | 50 | 1" BSP | | | | |
| F00554B00 | K150 METER LITERS - 1" BSP VER.B | D | 25-150 | 6,6-40 | A | 3,5 | 50 | 1" BSP | | | | |
| F00554C00 | K150 METER LITERS - 1" BSP VER.C | D | 25-150 | 6,6-40 | ▼ | 3,5 | 50 | 1" BSP | | | | |
| F00554D00 | K150 METER LITERS - 1" BSP VER.D | D | 25-150 | 6,6-40 | > | 3,5 | 50 | 1" BSP | | | | |