



PETROCAR 10 L/L

FUEL AND MINERAL OIL DELIVERY HOSE - LONG LENGTH



APPLICATION

Delivery hose for mineral oils, diesel fuel and gasoline with aromatic contents up to 50%

TUBE

Black, smooth, **NBR** rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Black, smooth, **NBR/PVC** rubber compound, resistant to oils, fuels, ozone and weather

WORKING TEMPERATURE

-13°F +176°F

-25°C +80°C

										
ID		OD		WEIGHT	WP		BP		BENDING RADIUS	COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	mm	m
4	5/32	10	3/8	0.10	10	150	30	450	40	100
5	3/16	12	15/32	0.12	10	150	30	450	40	100
6	1/4	13	1/2	0.13	10	150	30	450	50	100
7	9/32	14	35/64	0.14	10	150	30	450	60	100
8	5/16	15	19/32	0.17	10	150	30	450	65	100
10	3/8	17	43/64	0.20	10	150	30	450	80	100
13	1/2	20	25/32	0.24	10	150	30	450	105	50
15	19/32	23	29/32	0.32	10	150	30	450	120	50
19	3/4	27	1 5/8	0.39	10	150	30	450	150	50
25	1	35	1 3/8	0.63	10	150	30	450	200	50

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.