











ST 200 AC

# **FEATURES**

- · STURDY METALLIC FRAME
- READY TO USE
- EASY TO MOVE HEAVY DUTY

The PIUSI ST 200 AC is a dispenser that allows high flow refueling thanks to the two integrated E12O self-priming rotary electric vane pumps. Fitted with bypass valve and elevated reliability seal, the dispenser works even at low working temperatures and in every condition on worksites. The oval gear mechanical flow meter guarantees great precision (available on request). It is also available with wheels and handle (on request) for easier handling.

#### **PERFORMANCE**

UP TO 200 L/MIN FLOW RATE

AC CONTINUOUS DUTY POWER



ST 200 AC





# HANDY KIT: VERSION WITH WHEELS AND HANDLE

	PACKAGING											
	CODE	WE	IGHT	PACKAGING								
		KG	LBS	ММ	INCH	PCS/BOX						
	F00315000	46	101	587X395X42O	23,1X15,6X16,5	1						
[	F16860000	-	-	-	-	-						













TANK MONITORING

HOSE REEL

ACCESSORIES

MERCHANDISE













TEMPERATURE 13°C











WATER



CHART

Q = FLOW RATE (liter/min)

150

100

50

0




### IN THE BOX


- · ST 200 AC UNIT
- INSTRUCTION MANUAL

#### **DETAILS**



# **DIMENSIONS**





## MATERIALS

- · BODY: CAST IRON
- ROTOR: SINTERED STEEL
- · VANES: ACETAL RESIN
- SEAL: VITON
- SHAFT: STEEL

# Dimensions expressed in millimeters

TECHNICAL DATA												
	DESCRIPTION	FLUIDS TYPE	FLOW RATE		VOLTAGE		PUMP		MAX PRESSURE	OUTLET		
CODE			L/MIN	GPM	AC V./HZ DC VOLT	POWER WATT	AMP. MAX.	TYPE	N°	BAR	BSP	
F00315000	ST 200 BASIC	D	200	52,7	230/50	2050	10	E 120	2	2,5	1" 1/2	
F16860000	HANDY KIT (HANDLE + WHEELS)	D	-	-	-	-	-	-	-	-	-	