



Light-weight 12 Volt (DC) motor for drum pumps suitable for laboratories, service cars or smaller filling requirements. Ergonomic handle for an easy one-hand operation. Thermal overload protection ensure operational safety.

Technical Specifications

| | |
|-----------------------------|-------------------------------|
| Enclosure | Open Drip Proof (IP44) |
| Voltage | 12 V(DC) |
| Power Rating | 150 W |
| Nominal Current | 12,5 A |
| Frequency | 50-60Hz |
| Certification | CE |
| Housing Material | Thermoplastic Polyester Resin |
| Power Cord Length | 3 m |
| Power Cord Plug | DIN 4165 Plug or Clamps |
| Noise Level | 70 dBa |
| Thermal Overload Protection | Yes |
| Fixed Speed | 12.500 rpm |
| Weight | 2,0 kg |

Models Variants

| | |
|----------|----------------|
| SPE-12VA | DIN 4165 Plug |
| SPE-12VB | Battery Clamps |

Performance

| | |
|-------------------|-----------------------|
| Maximum Flow | 60 l/min |
| Maximum Head | 3 m |
| Maximum Viscosity | 200 mPas |
| Maximum Density | 1,2 kg/m ³ |

**measured with clean water at 21°. Pump Type: SP-PPS-39 drum pump*



Suitable for service cars, trucks, tractors, boats etc.